



# Vision

## ComboPlus

Automated sale of  
refrigerated products

## TECHNOLOGICAL INNOVATION

Vision ComboPlus features EasyFlex, an exclusive flexible extraction system. It stands out for the optimised capacity and volume, and its bespoke cooling unit that controls evenly the temperature inside the vendor, that allows storing and selling soft drinks in cartons, chocolate, healthy food items and similar products.

### FEATURES

- Temperature: Under 5°C.
- Capacity for 8 height-adjustable trays with up to 7 channels each.
- FIFO (First In First Out) System. Continues renewal with the freshest product. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting with on/off programming.
- 1462 x 473,5 mm glass front door.
- Continuous performance self-testing.
- Health timer: Automatic security system to prevent selling out-of-date products. Programmable expiration date by selection number or channel.
- Flexible setup and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 650 watts.
- Soft delivery elevator.

### STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- High-capacity cash box with lock and optional auto-locking during extraction.
- Injected foam insulation system that guarantees efficient cooling and lower energy consumption.

### CREDIT MANAGEMENT

- MDB or Executive protocol.
- Innovative coin mechanism with five return tubes for up to five different coin values and the most reliable fraud-prevention systems.
- Card and banknote readers can be fitted.

### PROGRAMMING

- General on site programming and display system for the data accounting, accessible from inside the machine.
- Compatible with the EasyFlash handheld terminal for stock control and accounting.
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.

### OPTIONS

- banknote reader.
- J130 card/key reader or any card reader that uses the MDB protocol.
- Pop-up billboard advertisement on the elevator.
- Vandal-proof coin entry.
- Modem installation and Vending Track communication interface.
- Online operation with real-time control of users and sales.
- Management of up to two slave vending machine for higher capacity and number of selections.
- External microwave ovens detached column controlled by the master machine. Self-activated when a product has been dispensed from the master machine. Individually heating time programmed per selection.

	COMBOPLUS
Temperature	Under 5°C
Maximum capacity	8 trays of up to 7 channels
Elevator	Yes
Size (mm)	1,830 x 803 x 935
Weight	325 kg
Energy supply	230 V, 50 Hz*
Cooling unit	CFC-free R-134a

\*Check for other voltages.



VANDAL-PROOF LOCK



OPTIMISED CAPACITY AND VOLUME



ENERGY-SAVING LED LIGHTING



BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS



EASYFLEX DELIVERY SYSTEM



HEALTH TIMER: EXPIRATION PROGRAMMING BY TEMPERATURE



PRODUCT DELIVERY DETECTION PHOTOCELLS



ELEVATOR



**Nesty**